

BoxSizer®

BX-600-LTS | Combination lid and tape closer

Standard technical specifications

Speed: Up to 10 boxes per minute (dependent on box height)**

Box footprint: Single footprint liddler / multi footprint tape closer

Closure: Glue/Lid and tape close†

Min box footprint: 320mm x 250mm (12.6" x 9.8")*

Max box footprint: 750mm x 500mm (19.7" x 29.5")

Typical max cut length: 410mm (16.1") (dependant on box height and width)

Typical infeed/outfeed height: 700mm (27.5")

Sample power consumption UK: 11Kw, 16A/Ph, 50Hz, 400V, 3 Phase, N&E

Sample power consumption USA: 11Kw, 16A/Ph, 60Hz, 480V, 3 Phase, N&E

Air consumption: Average 7.22 cfm @ 80-100 psi

Net weight: 1000Kg (2205lbs)

Specific components: Rockwell control system

Typical machine floorplan ref.: LS-26658

Touchscreen operator interface with management information and remote diagnostics

Emergency stops and safety circuitry, fully CE marked

Mild steel powder coated main frame

Low maintenance servo drives used for precision motion control and remote diagnosis

Box specifications

Box styles: HSC or FEFCO 0200/0300/0301. Preferred 0200/HSC.

Materials: B, C and E fluted corrugate of various grades typical, but not limited.

*Minimum box size will be half of largest box dimensions being run. **Speeds are typical, based on standard specification and is dependent on pitch and box height, actual production speed may increase/decrease from stated, bespoke options available. †Additional closure options available including: glue and tape, lidding, strapping and bagging. Note: Recommended maximum weight for loaded box 25Kg (55lbs).

For more information, contact: WestRock Automated Packaging Systems
Phone: +44.0.1502.713777 • E-mail: aps.uk@westrock.com • www.linkxpackaging.com

Options

A range of models are available with different closure options, including: tape, lidding and strapping.

Typical box infeed/outfeed with lid and tape closure

